



THE NEW ERA OF LAMINATION!

 $F L E \times A$

AUTOMATION FOR SIGN MAKERS



EASY LITE

Wide-Format Professional Laminator with integrated Wi-Fi/LAN.

It allows the Remote Monitoring of vital machine data

and working parameters via PC or mobile devices.



EASY LITE WITH WIFI CONNECTION THE NEW ERA OF LAMINATION!

The **Easy Lite** with Wi-Fi/LAN connection enters the era of **IoT (Internet of Things)**, a new way to make the machine more advanced and intelligent. Connected to the internet network, you can collect working data accurately and monitor operation remotely. This optimises the machine's performance, processes, durability and efficiency.

EASY TO USE NEW

Touch screen display and exclusive graphic design with intuitive settings of lamination parameters

REMOTE MONITORING VIA WI-FI/LAN

Useful for **scheduled maintenance** and avoiding machine downtime. Each inconsistent value is reported to the user and service

DESIGNED FOR YOUR NEEDS

New ergonomic solutions designed to facilitate the daily work (easy loading of rolls thanks to the new position of the shafts, lighter feed table, quick locking system of the shafts, motorized lifting of the roll)

EXCELLENT LAMINATION

The precise temperature, pressure and speed setting allows to obtain quality results

OPTIMISATION OF WORKFLOW

The **weekly scheduler** allows you to preheat the machine to the desired time and temperature. No waiting time, once arrived at the workplace

TIME SAVING NEW

Three default settings, that can be modified according to the requirements: helping to maintain quality on a consistent basis

NO MATERIAL WASTE

The integrated count function keeps track of total metres laminated

EVEN MORE PRECISE AND SAFE TRIMMING

New cutting unit with titanium coated blades, durable over time, for greater precision and long-term safety

FASTER PRODUCTION TIME NEW

Thanks to the optional that allows to work up to 10 m/minute

MADE IN ITALY

Designed and built in Italy exclusively with Italian components

LAMINATING WITH A TOUCH

The **innovative graphic design** of the software allows with **a simple touch** to set with **absolute precision** the most important parameters to achieve quality work, such as temperature, pressure and speed.

In addition, you can quickly access the **numerous new functions**, such as the storage of three different processes, the counting of metres laminated, the automatic shutdown, the weekly scheduler of switch on and off and much more.



Start screen of the processing menu



Setting of temperature, pressure and speed

<	(1
Laminated:	
565754 cm	Roll
To be laminated:	Starting length:
-565754 cm	5000 cm
At the end:	Remaining length:
Automatic stop	-3000 cm

Count function of total metres laminated



Three default settings (memories)



REMOTE MONITORING



Thanks to the Wi-Fi/ LAN module integrated in the machine, it is possible to connect to the Flexa Cloud and monitor the working data remotely on PC and mobile devices.

ADVANTAGES:

- Real-time access to machine vital data, working parameters and historical consultation
- Predictive maintenance: keep the laminator at maximum performance by reducing downtime and operating costs
- ✓ Fast and efficient diagnostics through service

APPLICATIONS

Signs - Floor graphics - Window graphics - Backlit display - Trade shows graphics - Pop-up - Stickers and pre-spaced stickers Rigid boards - Graphics for indoor flexible media - Table top displays - Car wrapping - Membrane keyboards - Many more...

CONFIGURATIONS

The new range of Easy Lite laminators with Wi-Fi/LAN module is available in two versions according to the needs.

	EASY LITE MODEL 1	EASY LITE MODEL 2
WJFI / LAN	✓	✓
Touch screen	✓	✓
Remote data monitoring	✓	
Total shafts Rear rewinding shaft (roll to roll)	4 Included	3 Optional (4)
Feed table	Aluminium	Aluminium
Rear worktop	Aluminium	Aluminium
Extra-deep feed table	Aluminium (Optional)	Aluminium (Optional)
Feed-in guide	✓	Optional
Front tray for prints	✓	Optional
Cutting unit	✓	Optional
Motorized lifting of the upper roller + Weekly scheduler: switch on/switch off	✓	Optional
Speed 10 mt/min	✓	Optional
Three default settings (memories)	✓	✓
Counter of metres laminated	✓	✓
Automatic stop	✓	✓
Bose Micro SoundLink® Bluetooth® speaker	✓	
Warranty	1 year + 12 months extra	1 year + 6 months extra



Touch screen display and control panel



Swing-up feed table for quick set-up



Aluminium extra-deep feed table with millimeter scale

Manufactured in compliance with CE regulations

O

39

You

Tube

in

CE

Follow us:



Wi-Fi antenna to communicate data with Flexa Cloud

Bose Bluetooth®

speaker



Front tray for single sheets



New cutting unit with titanium coated blades, safe for the operator, to trim the laminated media

Rewinding clutched shaft for adjusting the tension of the liner

_Unwinding braked shaft for adjusting the tension of the lamination film

Security sensor with emergency stop function for safety

Rewinding clutched shaft for adjusting _the tension of the laminated media

– Unwinding braked shaft for adjusting the tension of the media to be laminated



Aluminium extra-deep feed table ideal for mounting the graphic on the board

Feeding control by hand (control panel) or foot pedal (hand free operation)

Feed-in guide

	EASY LITE 110	EASY LITE 160
Working width	1100 mm (43 in)	1600 mm (65 in)
Max. space between rollers	50 mm (1,9 in)	50 mm (1,9 in)
Coated rubber rollers	Ø 120 mm (4,7 in)	Ø 120 mm (4,7 in)
Heated upper roll	Max. 60° C (140° F)	Max. 60° C (140° F)
Max. speed	5 m/min (16 ft/min)	5 m (16 ft)/min) (10 m (32 ft)/min optional)
Working height	900 mm (35 in)	900 mm (35 in)
Power supply	230 V - 50/60 Hz - 2000 W	230 V - 50/60 Hz - 2400 W
Dimensions (W x D x H)	1500 x 640 x 1585 mm (59 x 25 x 62 in)	2015 x 670 x 1585 mm (Model 1) (79 x 26 x 62 in) 2015 x 650 x 1585 mm (Model 2) (79 x 25 x 62 in)
Weight	211 kg (465 lbs)	255 kg (562 lbs) (Model 1) 240 kg (529 lbs) (Model 2)

Distributor

100% Made by FLEXA

100% Made in Italy

