



## TESIS R 1700-2300

### ROLL-SLITTER WITH ROTATING BLADE AND LOG REWINDER

Electrical sturdy and practical roll-slitter. It allows slitting of rolls and rewinding log rolls of different materials in an extremely precise and easy way.

- > Roll-slitter designed to slit rolls of different heights rapidly and accurately
- > The front unwinding shaft with brake allows rewinding log rolls converting new shorter length logs rolls of finished dimensions
- > Digital display of the cutting width and for rewound length (optional)
- > Digital display to stop the rewinding when the set dimension is reached
- > Easy loading device for heavy rolls changeover
- > Control system made by a PLC
- > Circular cutting blade Ø 315 mm ( 12 in.) with full protection with gradual uncovering during slitting process
- > Integrated lubrication system of the cutting blade

#### SUITABLE FOR:

- ☒ Vinyl film
- ☒ Coloured film
- ☒ Reflective material
- ☒ Application tape
- ☒ Double-side adhesive
- ☒ Protection film for lamination
- ☒ Printing media material
- ☒ Polyethylene
- ☒ Polypropylene
- ☒ Many more..





Comfortable hand grip with start push-button



Digital display for cutting measurement




Braking assembly for the cutting blade suggested for cutting fabrics and other particular materials (optional)




Pneumatic locking system of spindle

Electrical control panel display on small tower


Rewinding command controlled by foot pedal (hands free operation)



Rack with millimetric rod for fine adjustment



Easy scrolling of the cutting unit on chrome rod of Ø 50 mm (2 in.) with manual fastening



Easy rolls changeover thanks to the "ESABLOCK" locking system



Front unwinding shaft with brake to rewinding log rolls

	TESIS R 1700	TESIS R 2300
Working width	1700 mm (67 in.)	2300 mm (91 in.)
Maximum external roll diameter	Ø 210 mm (8 in.) - Ø 270 mm (11 in.) (changing the cutting unit - optional)	Ø 210 mm (8 in.) - Ø 270 mm (11 in.) (changing the cutting unit - optional)
Internal core of the roll	Ø 76 mm (3") standard Ø 50 mm (2") optional	Ø 76 mm (3") standard Ø 50 mm (2") optional
Adjustable cutting and unwinding speed with electrical inverter	from 0 to 200 rpm/min.	from 0 to 200 rpm/min.
Supply	230V - 50 Hz - 1500 W	230V - 50 Hz - 1500 W
Dimensions (W x D x H)	2550 x 900 x 1800 mm (100 x 32 x 71 in.)	3150 x 900 x 1800 (124 x 32 x 71 in.)
Weight	380 kg (838 lb.)	480 kg (1058 lb.)
Packing dimensions (W x D x H)	2650 x 1150 x 1970 mm (104 x 45 x 77 in.)	3450 x 1150 x 2000 mm (136 x 45 x 79 in.)
Packing weight	460 kg (1014 lb.)	620 kg (1367 lb.)



*It works with air compressor (not included). Silent oil free model provided by Flexa: 230 V - 50 HZ - 60 db*

#### Distributor

Manufactured in compliance with CE regulations



Follow us:



100 % Made by FLEXA



100 % Made in Italy