

## Available Dimensions

	Standard Values
Length	10/15/20/50 m
Width	650/1020/1270 mm
Thickness	0.6/0.9 mm


## Notice

Length 0.6mm: 10/20m (50m on demand)

Length 0.9mm: 10/15 m

## Description

- Magnetic Film laminated with white matt PVC, compatible for UV curable and Screen printing
- To be used in combination with iron or steel surfaces (e.g. Aluwel Steel Composite Sheets), easy to apply, remove and change, without leaving residues
- No demagnetizing, no rusting



## Technical Data

	Max-Jet 0.60 mm	Max-Jet 0.90 mm
Pull Strength	≥24 g/cm <sup>2</sup>	≥41 g/cm <sup>2</sup>
Gauss	≥260 Gs	≥ 310 Gs
Thickness	0,6mm (±0.06)	0,9mm (±0.09)
Weight	2400 gsm (±100)	3500 gsm (±100)
Water Resistance	High	High
Opacity	100%	100%
Application Temp.	temperature 15°C to 30°C , and relative humidity 30% to 60%.	temperature 15°C to 30°C , and relative humidity 30% to 60%.
Resistance Temp.	temperature change is within 40°C daily	temperature change is within 40°C daily

## Print Compatibility

compatible	testing required	not compatible
Soft UV Ink	Eco Solvent	Latex / Toner      Dye/Pigment
Screen Print	Offset/ Flexo	

## Storage

Storage conditions: in closed original packing avoiding sunlight, in temperatures of 10°C to 35°C, relative humidity 20% to 70%.

Shelf life: 12 months from production date under above storage conditions. Unfinished material should be seal-packed, and used up within one month.