

B-FLEX ITALIA S.r.l.

Via 1° Maggio, 44
36050 Sovizzo (VI) ITALY
Ph +39 0444.028139
info@b-flexitalia.com

www.b-flexitalia.com

follow us on   

BF PRINT REF

PRODUCT DESCRIPTION

BFPRINTREF is a reflective heat transfer film, printable with solvent, eco-solvent and latex inks, suitable for heat transfer on cotton fabrics, polyester and acrylic garments.

Thanks to its opacity BF PRINTREF can be used on both light and dark garments and can be pressed on T-shirts, sportswear or uniforms for work.

APPLICATION INSTRUCTIONS

- Print BF PRINTREF
- Wait at least 8 hours after printing, before proceeding cut.
- Cut BF PRINTREF with a laser 45° blade.
- Weed the BF PRINTREF and remove the excess materials.
- Place the BF MYLAR film on the graphic and remove the air bubbles.
- Take off the graphic from the polyester backing.
- Pre-heat your press to 150 ° C.
- Place the garment on the lower platen of your heat press.
- Place the BF PRINTREF design on the garment.
- Press at 150 ° C for 10 seconds.
- Peel the BF MYLAR.

STANDARD SIZES

- H 150 cm => available lengths:
(upon request)
- H 100 cm => available lengths:
(upon request)
- H 75 cm => available lengths:
(upon request)
- H 50 cm => available lengths:
25 mt / 12,5 mt / 5 mt / 1 mt (standard)

APPLICATIONS TIPS

- Recommended fibers: organic, synthetic, mixed
- Ability to cut designs as small as 1.0 cm

TECHNICAL DATA

Film:	PU / Polyurethane
Thickness:	150 μ (±5%)
Carrier:	PET film – self adhesive

APPLICATION

Temperature:	150°C - 305° F
Time:	10"
Pressure:	medium – 3,5 bar – 50 PSI

LINER REMOVAL

Warm; wait 5-7 seconds after application

WASH RESISTANCE

First wash:	wait 12 hours after application
Max wash Temp.:	40° C
Dry clean:	NO
Softener:	NO
Bleach:	NO
Dryer:	NO

SAFETY NOTICE

The values reported in this document are average values as tested under normal conditions in our lab. We cannot provide a guarantee regarding the information abovementioned in this page.

Due to possible variations in the production of garments, B-FLEX recommends testing the material prior to all applications.

This spec sheet is valid for the following products:

BF PRINTREF. Rev_2019 / 09.