



B-FLEX ITALIA S.r.l.

Via 1° Maggio, 44
36050 Sovizzo (VI) ITALY
Ph +39 0444.028139
info@b-flexitalia.com

www.b-flexitalia.com

follow us on   

BF NYLON



BF NYLON

PRODUCT DESCRIPTION

Thanks to its specially formulated heat-sensitive adhesive, BF NYLON is ideal to be applied on nylon and similar fabrics (jackets, K-Way, duffel bags, umbrellas, shoes, backpacks, travel bags, lanyards, etc.). Thanks to its improved adhesion, this product guarantees that your application will last over time.

This product is easy to work with; the sticky polyester carrier allows for fast weeding and easy repositioning of details that might have accidentally been removed.

BF NYLON can be layered with itself or other B-FLEX films.

APPLICATION INSTRUCTIONS

- Mirror cut BF NYLON, with a 45° blade
- Weed BF NYLON and remove all excess material.
- Pre-heat your press to 145°C.
- Place the garment on the lower platen of your heat press.
- Place your BF NYLON design on the garment.
- Press at 145°C for 12 seconds.
- Wait 5-7 seconds before peeling the carrier.

STANDARD SIZES

- H 150 cm => available lengths:
25 mt (upon request)
- H 100 cm => available lengths:
25 mt (upon request)
- H 75 cm => available lengths:
25 mt (upon request)
- H 50 cm => available lengths:
25 mt / 12,5 mt / 5 mt / 1 mt (standard)

APPLICATION TIPS

- Recommended Fibers: Nylon and Similar Fibers.
- Not recommended for layering.
- Can be applied with other B-FLEX films (ex. FATTY, GLITTER, FLOCK, etc.)
- Ability to cut designs as small as 0.25 cm
- Doesn't require a Teflon sheet during the pressing phase.

TECHNICAL DATA

Film:	PU/ Polyurethane
Thickness:	75 μ (±5%)
Carrier:	Adhesive PET

APPLICATION

Temperature:	145°C - 295° F
Time:	12"
Pressure:	medium – 3,5 bar – 50 PSI

LINER REMOVAL

Warm; wait 5-7 seconds after application

WASH RESISTANCE

First Wash:	12 hours after application
Max. Wash temperature:	40° C
Dry Clean:	NO
Softener:	NO
Bleach:	NO
Dryer:	NO

SAFETY NOTICE

The values reported in this document are average values as tested under normal conditions in our lab. We cannot provide a guarantee regarding the information abovementioned in this page.

Due to possible variations in the production of garments, B-FLEX recommends testing the material prior to all applications.

This spec sheet is valid for the following products:
BF NYLON. Rev_2019/09_EN