

Substrate		DIN 60001	100 % polyester
Weave		DIN ISO 9354	woven fabric
Weight approx.		DIN EN ISO 2286-2	300 g/m ²
Fire retardancy		DIN 4102 B1, ÖNORM A3800, NFPA 701, CA 1237	yes
Application			indoor, outdoor (short-term)
Width		DIN EN ISO 2286-1	max. 308 cm / 121 inch (see overview)
Print side			width < 3 m: print side outside width > 3 m: print side inside
Roll length			30 - 50 ± 0,5 m
Type of ink			all kinds of solvent inks, UV-curable inks, latex inks*

Advantages

- high tear resistance
- no curling
- fast crease recovery
- easy to clean
- dirt-repellent
- trimming cold (no fraying)

Applications

- roll up
- banner
- frontlit
- roller, vertical, panel blind

* not for outdoor use

made in Germany

All details are nominal values and are subject to change within usual tolerances (± 5 %). The information provided in this document is based on current knowledge and experience. They do not exempt a manufacturer/processor from carrying out their own tests and trials as their in-house handling and manufacturing processes can have a significant range of influences on outcomes. Application, utilisation and processing of products is taking place outside of our control and are therefore the sole responsibility of the manufacturer/processor. date: 01/2020

