Product Bulletin

Concept® 223

SEMI RIGID WHITE MATTE PVC Removable Adhesive

Concept[®] 223 is a 150 mic premium white matte semi rigid polymeric vinyl film coated with 200-4982 removable acrylic pressure sensitive adhesive laminated to a 135 gsm tight release digital liner designed for roll processing. This film is designed to accept a variety of solvent-based, UV curable and latex inks common to wide format digital printing systems.

Applications Concept® 223 is a high performance removable decal film designed for ease of

application of temporary interior or exterior signage, decals, nameplates, die-cut letters and point-of-purchase displays. Concept® 223 is the ideal media for temporary store front applications requiring bond to windows. This media may also be used on smooth surfaces such as metals, painted metals and certain high energy plastics. Not

designed for coated/ sealed/ treated stainless steel, brass or bronze surfaces.

Thickness Film 150 mic.

Adhesive 25 mic Liner 135 gsm

(Thickness variance +/- 10%)

Dimensional Stability Good.

Temperature Ranges Minimum application temperature +4,4°Celsius

Service temperature -40°C bis +82°C.

Expected Exterior Exposure Removable up to 1 year under normal conditions.

Adhesion To glass 1,09 bis 4,38 N/25mm

To standard test panels 1,09 bis 4,38 N/25mm

Tested according to PSTC-101 Method A with 24-hour dwell at 21°C and 50% relative humidity. Typical values. Individual values may vary. Test thoroughly before

production.

Water Resistance Good. Test if immersed.

Humidity Resistance Good

Solvent Resistance Good

Storage Stability 6-month shelf life when stored at 21°C and 50% relative humidity

Product Series E223-54 1,37m x 30.48m

Recommendations Completely evaporate inkjet solvents before application. Failure to do so may facilitate

solvent penetration resulting in vinyl degradation.



Manufacturer of Pressure Sensitive Films, Traffic Graffic Floor Advertising Films, Custom Coatings and Printing Inks.

309 S. Union • P.O. Box 158 • Sparta, Michigan 49345 • (616) 887-7387 • (800)253-3664 • FAX (616)887-0537

Web Site: $\underline{www.general formulations.com} \bullet e-mail: \underline{gfiinfo@general formulations.com}$