Product Bulletin

Concept® 400 HIGH GLOSS UV OVERLAMINATING FILM

Concept[®] 400 Gloss UV Overlaminating Film is a pressure sensitive 75 MIC high gloss optically clear PVC film offering resistance to ultra violet degradation with the 200-4990 permanent acrylic adhesive on a smooth liner. This vinyl film protects the graphics from abrasion, moisture and ultra violet radiation. It is laminated by the cold laminating process without the addition of heat.

Applications	Concept [®] 400 gloss overlaminating vinyl film is designed to protect digital image prints and screen printed images for exhibit and display graphics. Can be used in most instances where an overlay with a high gloss finish is required on interior or exterior applications.	
Thickness	Film Adhesive Liner (Thickness variance +/- 10%)	75 mic. 25 mic 80 gsm
Dimensional Stability	Good.	
Temperature Ranges	Mindestanwendungstemperatur Einsatztemperaturbereich	+4,4°Celsius -40°C bis +82°C.
Expected Exterior Exposure	Up to 4 years under normal conditions (Vertical Surfaces)	
Adhesion	To stainless steel	13,13 N/25mm
	Tested according to PSTC-101 Method A procedure with 24 -hour dwell at 21°C and 50% relative humidity. Typical values. Individual values may vary. Test thoroughly before production.	
Light Transmission	Approximately 90% @ 550 nm	
Gloss 20 Gardner	Initial ≥ 60	
Storage Stability	1-year shelf life when stored at 21°C and 50% relative humidity.	
Product Series	E400-54 1,37m x 50m	



Manufacturer of Pressure Sensitive Films, Traffic Graffic Floor Advertising Films, Custom Coatings and Printing Inks.

309 S. Union • P.O. Box 158 • Sparta, Michigan 49345 • (616) 887-7387 • (800)253-3664 • FAX (616)887-0537 Web Site: www.generalformulations.com • e-mail: gfiinfo@generalformulations.com

1,52m x 50m

E400-60

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to General Formulations, Inc's Price List for Terms and Conditions or Sale, Including Disclaimer of Warranties and Limitation of Liability.