EMBLEM Floorgraphics

FLOGRA is a special laminate for the guarding of prints for floor advertising. The structured surface of the film assures the anti-slip protection (R11).

Matchcode:	FLOGRA
Material:	PVC
Finish:	structured matt
Color:	transparent
Thickness:	170 µm
Adhesion:	permanent, solvent-free, polyacrylate
Liner:	one side siliconized,white, glassine paper, 63 g/m²
Adhesion:	11 N / 25mm (acc. to AFERA5001 - 24h average value)
Appl. temperature:	> +15°C
Temperature resistance:	from -40°C to +80°C
Width of roll:	104 cm, 130 cm
Length of roll:	50 meters
Anti-Slip property:	R 10 acc. DIN 51130
Storage:	cool and dry enviromnt at 15 - 25°C, 50% rel. humidity
Durability:	24 months in original boxes

Different printers, inks, resolutions and printing qualities result into numerous different printing parameters. In addition, there a numerous factors influencing processing and the application of our materials. For this reason, we cannot make specific statements as to drying times and maximum ink absorption. For this reason, we recommend you to perform own tests in order to verify the desired results. Our product specifications are not to be understood as legally binding guarantees assuring specific characteristics. Any liabilities and guarantees, as well as claims for compensation beyond the value of the product itself are excluded.

DATAPLOT
SINCE 1979

Gutenbergstraße 15 · D-24558 Henstedt-Ulzburg · Telefon: +49 41 93-99 50 · Telefax: +49 41 93 - 99 52 20
E-Mail: info@dataplot.de · Internet: www.dataplot.de

EMBLEM-Datenblaetter Laminate en way; Geändert: 14.11.14

EMBLEM Floorgraphics

Description:

FLOGRA is a special laminate for the guarding of prints for floor advertising. The structured surface of the film assures the anti-slip protection (R11).

This product is especially made for indoor use. Using edge protection it is qualified for outdoor use up to one year.

The permanent glue has been developed extra for laminating films. It could be used for cold lamination.

Due to this the glue has excellent protection against humidity, aging and solvents. Materials equipped with this adhesive film can be repositioned on most surfaces.

To avoid fingerprints the use of cotton-gloves is advisable.

Typical Applications:

Finishing floor advertising