

GEKKOTEX

150 mic

Material Description

GEKKOTEX is a Self Adhesive Polyester Fabric that can be installed on virtually any surface and then removed and reused many times over. The adhesion will not leave a residue on the surface when it's removed. GEKKOTEX is revolutionizing the marketplace when it comes to dressing public and commercial spaces. GEKKOTEX the easiest way to change the visual appeal a of space. From cafes, bars and restaurants to high-street retail stores... the market and creative possibilities with GEKKOTEX are as wide as your own imagination!

Qualifications

- Semi-matte surface
- Denier: 150D x 150D
- core: 3"
- standard length: 30m
- standard width: 1270mm & 1370mm
- 90g PE coated paperadhesive on the back side, acryl based (weak and strong adhesive)

Applications

- Wall Covering
- Stand building
- Indoor decoration






The possibilities and opportunities are endless...!

Physical Properties

Quality		100% Self Adhesive Woven Polyester Fabric
Material		Polyester
Thickness		150 mic ASTM D645
Weight		97 g/m ² ASTM 646
Total Thickness		335 mic
Peel Strength (180°, kgf/2.54cm)	20min	0.7 ≤ 0.78 ASTM D903
	24 h	0.9 ≤ 1.02 ASTM D903
Holding Power	Minute	60 ≤ ASTM D3654 at 60C
Tensile Strength (kgf/mm ²)	MD 45 ≤	50.4 ASTM D882 (Except Release Paper)
	TD 35 ≤	40.4 ASTM D882 (Except Release Paper)

Compatibility

**Hewlett Packard
Epson
Mutoh
Mimaki
Roland
And more...**

-  Eco Solvent
-  Solvent
-  Latex
-  UV-curable
-  UV-curable Led
- Water
- Oil
- Dye-sublimation

Make your own practical test to be sure it reaches your quality standard. For all- and latest information see our Compatibility List.

Printing guidelines

Max. temperature (material) should not exceed 80°C as overheating can impair the flatness of the media. Ink restrictions and heater settings have to be set for specific printer ink combinations to obtain the best results.

Colour profiles

AT graphix develops high quality ICC colour profiles for the divers printing media's. We work with specialists that can do this service for almost every printer - rip combination

Storage conditions

1 year under normal conditions (10–25°C at a relative humidity of 30–75 %). Higher humidity and/or temperature can affect the product performance. Always store the media in a dark place.

Environment

The media and final prints can be disposed of as paper waste. Material is suitable for recycling. Please consult local recycle resources. For treatment of ink or ink residue, please refer to your printer manual or supplier.