

# H63210 | ULTRA Satin 170

MICROPOROUS RESIN-COATED PAPER

## PRODUCT SPECIFICATION \*

<b>Weight</b> DIN EN ISO 536	g/m <sup>2</sup>	171	± 6
<b>Thickness</b> DIN EN ISO 534	µm	176	± 6
	mil	6.9	± 0.2
<b>Gloss BYK (60°)</b> ISO 2813		19	± 5
<b>Colour Elrepho UVO (D65)</b> ISO 2469	L	94,1	± 0,8
	a	-0,2	± 0,5
	b	-2,0	± 0,8
	delta b	10,5	± 0,8
<b>MLD UVO</b>	L	91,6	± 0,5
	a	-0,5	± 0,3
	b	-2,4	± 0,5
	delta b	11,2	± 0,8
<b>CIE whiteness (D65/10°) min.</b> ISO 2469		> 140	
<b>Opacity min.</b> ISO 2469	%	> 89	

### Printability

Simplex printable

### Laminatability

Hot & cold

### Printing Technology

💧 Inkjet water-based

### Compatibility

Can be used on all commercial thermal, piezo water-based printing systems like Epson, Canon, Hewlett-Packard, Kodak, Encad etc.

## BENEFITS & PROPERTIES

- Pin-sharp details
- Vivid colours
- High colour consistency and gamut
- High opacity
- High light fastness
- Water resistance
- Outstanding lay-flat performance

## KEY APPLICATIONS

### Sign & Display Graphics

- POS signage
- Exhibition graphics
- Photo prints
- Commercial posters for indoor and short-term outdoor applications

### Wall Decoration

- Poster
- Large-format photo prints

### Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

\* Modifications reserved.

Version 02/2016