

Material Description Textile fabric backed matt GOLD & SILVER vinyl wall covering 360gsm(*) Specially formulated acrylic lacquer with exclusive inkjet receiver layer. Wallpaper and image can be protected by clear acrylic overcoat by machine or roller Available in 2 different finishes... GOLD & SILVER with embossing. The possibilities and opportunities are endless. No more empty walls to stare at. Bring the living spaces alive with a stylish ambience. The market and creative possibilities with a wall-covering are as wide as your own imagination!

- Qualifications**
- Lightfastness 7 * 8.
 - Imo quality (Lloyd's)
 - UV-protected*
 - Easy to clean with mild soap
 - Scrubbable (**) EN 259-1 / EN 12956
 - Available in 1300mm x 50m
 - Packaging in craft paper and box.
 - Resistant to mould bacteria
 - ISO 14001, IGI Quality Mark
 - Integrated Pollution Prevention and Control (IPPC)

- Fire ratings**
- Fire ratings: B – s1 – d0 EN 13501-1
 - Class 0/1 BS 476 part6/7 I
 - MO (***) A.653(16)
 - IMO (***) MSC 61(67) annex 1 part 5/annex 2
 - B1(****) DIN 4102 – 01
 - M1 NFP 92501/92507

Application tips In general: Digitally printed wall covering can be washed. Slight or moderate soiling can be removed using a combination of mild detergent and a damp cloth. Dabbing (certainly not Rubbing) is recommended to lift the soil. Bleach, abrasive cleaners and similar compounds must not be used. Resistant to: Soap, Detergents, Alcohol, Ammonia, Alkali, Diluted acids
Not resistant to: Solvents, Esters, Aromatic hydrocarbons

Applications (*) = Higher weights possible on demand
(**) = Depends on embossing / structure
(***) = Certificate numbers: 164.112/1121/WCL
(****) = ABP number: P-MPA-E-04-50

Physical Properties

Quality		Vinyl attached to paper.
Weight*	EN ISO 2286-2	360 g/m ² +/- 20 g/m ² depending on embossing
Thickness **	EN ISO 2286-3	0,32 depending of embossing
Print side		Matt vinyl with embossing
Reverse side		Paper
Fire retardant	EN 13105-01	Euro class B
Ship building		IMO quality (Lloyds's)
Light fastness	EN ISO 105-b02	7 * 8

Compatibility **UV, Solvent & Eco Solvent Printing system:**
LATEX & HP, Epson, Roland, Mimaki, Mutoh, Seiko, Oce

 UV Curable
 Solvent
 Latex

Make your own practical test to be sure it reaches your quality standard.
For all- and latest information see our Compatibility List.

Printing guidelines Ink restrictions and heater settings have to be set for specific printer ink combinations to obtain the best results.

Colour profiles ATgraphix develops high quality ICC colour profiles for the divers printing media's. We work with specialists who can produce your profile if it's not direct available from our library. Please contact us for the possibilities.

Storage conditions 1 year under normal conditions Higher humidity and/or temperature can affect the product performance. Always store the media in a dark place. Storage condition: temperature 10-25° / relative humidity 50%

Environment The media and final prints can be disposed as PVC. Material is suitable for recycling. Please consult local recycle resources.