

PRODUCT DESCRIPTION

BF WINDSTOP is a polyurethane Heat Transfer Vinyl for application on softshell garments. Thanks to its application temperature of just 110°C, this film is perfect to decorate waterproof jackets, hats, shoes, and other synthetic fibers with graphics and logos. The film is fully opaque thanks to its built-in barrier. This allows you to print light colors on dark textiles and also prevents dye migration on sublimated garments. BF Windstop is easy to work with.

The cutting lines are highly visible which makes the weeding process simple and quick. The sticky polyester carrier allows to reposition any letter that was accidentally misplaced.

APPLICATION TECHNIQUES

- Knockout
- Layering from other series

APPLICATION STEPS

- Cut - 45° blade
- Weed excess material
- Turn on your heat press - heat to 110°C/230°F
- Place your graphic on the garment
- Press it - 110°C/230°F for 8 seconds
- Remove the liner - hot

SIZES

H 50 cm L 20 mt / 10mt / 5 mt / 1 mt

H 75 cm L 20 mt (upon request)

H 100 cm L 20 mt (upon request)





H 150 cm L 20 mt (upon request)

Comply with
regulation **REACH**
n°1907/2006/EU




SAFETY NOTICE

The values reported in this document are average values as tested under normal conditions in our lab. We cannot provide a guarantee regarding the information abovementioned in this page. Due to possible variations in the production of garments, B-FLEX recommends testing the material prior to all applications. Rev_2021/03






TECHNICAL DATA

	Film: PU/polyurethane
	Thickness: 180µ (±5%)
	Liner: adhesive PET
	Finish: matte

PLOTTER SETTING

	Cut settings: mirror
	Blade: 45°
	Minimum cut: 1 cm

APPLICATION

	Temperature: 110°C - 230°F
	Time: 8''
	Liner removal: hot
	Pressure: medium - 3,5 bar - 50 PSI
	Textile: Softshell, synthetic, treated fabrics, sublimated fabrics

WASH RESISTANCE

First wash after application	wait 12 hours
Max wash temperature	40°C - 104°F
Dry clean	✗
Dryer	✗

BF WINDSTOP

COLOUR GUIDE



- Application on Softshell and technical garments
- Sublistop
- Fully opaque



BF W700A
WHITE WINDSTOP



BF W792A
GOLD WINDSTOP



BF W796A
SILVER WINDSTOP



BF WFLU020A
NEON YELLOW WINDSTOP



BF WFLU030A
NEON ORANGE WINDSTOP



BF WFLU040A
NEON PINK WINDSTOP



BF WFLU050A
NEON GREEN WINDSTOP

